






Three Phase String Inverter

SUN-4/5/6/7/8/12K-G06
SUN-10K-G05




NEO

-  2 MPP trackers, Max. efficiency up to 98.3%
-  Zero export application, VSG application
-  String intelligent monitoring (optional)
-  Wide output voltage range
-  Anti-PID function (Optional)

Technical Data

Model	SUN-4K-G06	SUN-5K-G06	SUN-6K-G06	SUN-7K-G06	SUN-8K-G06	SUN-10K-G05	SUN-12K-G06
PV String Input Data							
Max. PV Input Power (kW)	5.2	6.5	7.8	9.1	10.4	13	15.6
Max. PV Input Voltage (V)	1100						
Start-up Voltage (V)	140						
MPPT Voltage Range (V)	120-1000						
Rated PV Input Voltage (V)	600						
Max. Operating PV Input Current (A)	13+13						
Max. Input Short Circuit Current (A)	19.5+19.5						
No. of MPP Trackers/ No. of Strings per MPP Tracker	2/1+1						
AC Output Side							
Rated AC Output Active Power (kW)	4	5	6	7	8	10	12
Max. AC Output Apparent Power (kVA)	4.4	5.5	6.6	7.7	8.8	11	13.2
Rated AC Output Current (A)	6.1/5.8	7.6/7.3	9.1/8.7	10.7/10.2	12.2/11.6	15.2/14.5	18.2/17.4
Max. AC Output Current (A)	6.7/6.4	8.4/8	10/9.6	11.7/11.2	13.4/12.8	16.7/16	20/19.2
Rated Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un						
Grid Connection Form	3L/N/PE						
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65						
Power Factor Adjustment Range	0.8 leading to 0.8 lagging						
Total Current Harmonic Distortion THDi	<3%						
DC Injection Current	<0.5%In						
Efficiency							
Max. Efficiency	98.1%	98.2%			98.3%		
Euro Efficiency	97.5%	97.6%			97.8%		
MPPT Efficiency	>99%						
Equipment Protection							
DC Polarity Reverse Connection Protection	Yes						
AC Output Overcurrent Protection	Yes						
AC Output Overvoltage Protection	Yes						
AC Output Short Circuit Protection	Yes						
Thermal Protection	Yes						
DC Terminal Insulation Impedance Monitoring	Yes						
DC Component Monitoring	Yes						
Ground Fault Current Monitoring	Yes						
Power Network Monitoring	Yes						
Island Protection Monitoring	Yes						
Earth Fault Detection	Yes						
Overvoltage Load Drop Protection	Yes						
Residual Current (RCD) Detection	Yes						
Surge Protection Level	TYPE II(DC), TYPE II(AC)						
Interface							
Communication Interface	RS485/RS232 /WiFi/LAN						
General Data							
Operating Temperature Range (°C)	-25 to +60°C, >45°C Derating						
Permissible Ambient Humidity	0-100%						
Permissible Altitude (m)	4000m						
Noise (dB)	<45						
Ingress Protection(IP) Rating	IP 65						
Inverter Topology	Non-Isolated						
Over Voltage Category	OVC II(DC), OVC III(AC)						
Cabinet Size (WxHxD mm)	283×463×178 (Excluding Connectors and Brackets)						
Weight (kg)	11						
Warranty	5 Years						
Type of Cooling	Natural Cooling						
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105						
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2						